



Green Pin® Dee Shackles


with square sunken hole screw pin



- **Material** : bow and pin high tensile steel, Grade 6, quenched and tempered
- **Safety Factor** : MBL equals 6 x WLL
- **Standard** : meets performance requirements of US Fed. Spec. RR-C-271, Grade A
- **Finish** : hot dipped galvanised
- **Certificates** : this product is supplied with a works certificate as standard, also upon request a basic raw material, manufacturer test certificate and/or EC declaration of conformity
- **Note** : key for unscrewing the pin must be ordered separately



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length bolt	length hole	size hole	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
2	13.5	16	34	13.5	22	43	85	51	10	0.34
3.25	16	19	40	16	27	51	105	53	10	0.60
4.75	19	22	47	19	31	59	125	74	10	0.98
6.5	22	25	53	22	36	73	144	85	12	1.26
8.5	25	28	60	25	43	85	161	99	12	2.14
9.5	28	32	67	28	47	90	179	110	16	3.05
12	32	35	74	32	51	94	199	122	16	3.56
13.5	35	38	80	35	57	115	220	135	16	5.17
17	38	42	89	38	60	127	239	145	16	6.84



In inch



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length bolt	length hole	size hole	weight each
tons	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	lbs
2	1/2	5/8	1 11/32	17/32	7/8	1 23/32	3 11/32	2	3/8	0.75
3.25	5/8	3/4	1 19/32	5/8	1 3/32	2	4 1/8	2 3/32	3/8	1.33
4.75	3/4	7/8	1 7/8	3/4	1 1/4	2 5/16	4 29/32	2 29/32	3/8	2.15
6.5	7/8	1	2 3/32	7/8	1 7/16	2 7/8	5 11/16	3 11/32	1/2	2.77
8.5	1	1 1/8	2 11/32	1	1 23/32	3 11/32	6 5/16	3 29/32	1/2	4.72
9.5	1 1/8	1 1/4	2 5/8	1 1/8	1 7/8	3 9/16	7 1/32	4 5/16	1/2	6.72
12	1 1/4	1 3/8	2 29/32	1 9/32	2	3 23/32	7 13/16	4 13/16	5/8	7.84
13.5	1 3/8	1 1/2	3 5/32	1 3/8	2 1/4	4 17/32	8 11/16	5 5/16	5/8	11.40
17	1 1/2	1 5/8	3 1/2	1 17/32	2 11/32	5	9 3/8	5 3/4	5/8	15.08

